

Z-Perform™ 1000D Label

Direct thermal, phenol-free, paper label with permanent acrylic adhesive

Many thermal materials utilize phenol developers, such as BPS or BPA, which studies have shown can negatively impact users' health. Zebra's Z-Perform 1000D label, however, offers you a unique alternative. This direct-thermal paper label is engineered with Vitamin C as its developer, offering an ideal substitute to phenols, while delivering the performance you have come to rely on from Zebra's Z-Perform family. The Vitamin C developer creates an orange tone to the material, which enables your brand to stand out from the crowd as an environmentally conscious global partner. The permanent acrylic adhesive can be applied to surfaces as cold as -4° F/-20° C. And with Zebra's legacy of craftsmanship and durability, you can count on optimized performance — with each and every label. Z-Perform 1000D labels are recommended for a wide variety of labeling applications including shipping, receiving, and work-in process.



Count on Consistently Exceptional Performance with Zebra Certified Supplies

Printing supplies can impact everything from printhead lifespan to operational efficiency. That's why we design, produce and rigorously pre-test our own line of thermal printing supplies to ensure consistent, optimized performance. We utilize an ISO 9001 certified, 23-point quality inspection to ensure consistent quality — and we never swap out materials. No matter when you order your labels, you can count on the same great performance.

Phenol-Free

Many thermal supplies use phenols as developers. Phenols are considered by some to be dangerous chemicals that have the potential to lead to adverse health conditions. Zebra's Z-Perform 1000D material offers a phenol-free labeling solution while delivering the performance you have come to expect from Zebra Certified Supplies.

Utilizes Vitamin C as a Developer

The Z-Perform 1000D label features an innovative, direct thermal paper facesheet that uses an alternative, phenol-free developer — Vitamin C. The orange tone on a label is easily recognizable as phenol-free, offering your company the opportunity to promote yourself as an environmentally conscious global partner, as well as a company looking out for the health and well-being of its stakeholders.

Ensure Long-Term Adhesion for a Variety of Applications

With its permanent acrylic adhesive that offers excellent adhesion on corrugated packaging, Z-Perform 1000D labels are ideal for a wide variety of indoor applications in shipping, logistics, and warehousing.

Z-Perform 1000D — Phenol-free direct thermal label that delivers reliable performance.
For more information on the Zebra's Z-Perform 1000D labels,
please visit www.zebra.com/supplies

Specifications

Material Construction	
RM Number	65832RM
Facestock	Uncoated direct thermal paper 2.1 mil
Adhesive	Permanent acrylic adhesive 0.8 mil
Liner	40 lb semi-bleached kraft stock 2.4 mil
Total Thickness (+/- 10%)	5.3 mil
Environment	Indoor use
Temperature Performance	
Minimum Application Temperature¹	38°F/3°C
Service Temperature Range²	-65°F to 200°F/-54°C to 93°C
Recommended Printers and Ribbons	
Printers	Direct thermal printer; use Zebra mobile and desktop mid-range and high-performance thermal printers for optimal performance
Ribbons	N/A
Adhesive Strength	
Corrugate	5 minute dwell time: * 24 hour dwell time: *
Steel	5 minute dwell time: * 24 hour dwell time: *
Polycarbonate	5 minute dwell time: * 24 hour dwell time: *
Polyethylene	5 minute dwell time: * 24 hour dwell time: *
* Indicates that attraction between adhesive and surface is so great that the facestock rips. Tests performed at room temperature.	
Chemical Resistance	
Weak Chemicals	
Blood	Test in your application
Body Fluid	Test in your application
Salt Water	Test in your application
Water	Test in your application
Window Cleaner	Not Recommended
Moderate Chemicals	
Alcohol	Test in your application
Ammonia	Test in your application
Bleach	Test in your application
IPA	Test in your application

Harsh Chemicals	
Gasoline	Not Recommended
Grease	Not Recommended
Extreme Chemicals	
Acetone	Not Recommended
Grease	Not Recommended
IR Reflow	Not Recommended
MEK	Not Recommended
TCE	Not Recommended
Xylene	Not Recommended
Regulatory and Compliance	
Paragraph of Information	Meets FDA 175.105 for indirect food requirements
Product Performance & Suitability	
Recommended Storage Conditions	72°F /22°C at 50% RH
Expected Life Span in Application	Indoor use, for 1 year
Material Testing in End Application	
The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.	
Footnotes	
1. When the label is applied, the environment and surface should be above this temperature. 2. Following correct application and appropriate dwell time (usually 24hrs) the media will withstand this temperature range.	

Markets and Applications

Transport & Logistics

- Shipping and receiving

Manufacturing

- Product identification receiving

Retail

- Price markdown labels



NA and Corporate Headquarters
+1 800 423 0442
inquiry4@zebra.com

Asia-Pacific Headquarters
+65 6858 0722
contact.apac@zebra.com

EMEA Headquarters
zebra.com/locations
contact.emea@zebra.com

Latin America Headquarters
zebra.com/locations
la.contactme@zebra.com